

SILENCERCO SAKER ASR

FIELD MANUAL

WE AT SILENCERCO® HOPE THAT YOU ENJOY THE TECHNOLOGICAL
Thank you for choosing to add a SilencerCo silencer to your collection. We
manufacture all of our products under one roof here in the USA and are proud to
deliver only the best silencers to our community. We hope you will enjoy using this
product as much as we enjoyed making it and welcome to our family.

Sincerely and Silently,



JOSHUA WALDRON

SilencerCo Co-Founder & CEO

TO PROVIDE FOR YOUR SAFETY AND THE EFFECTIVE USE OF THIS
SUPPRESSOR, IT IS CRITICAL THAT THE OWNER AND ANY USER OF THE
SUPPRESSOR READ THIS ENTIRE MANUAL AND FOLLOW STRICTLY THE
WARNINGS AND INSTRUCTIONS WITHIN. THIS SUPPRESSOR IS INTENDED
TO BE USED ONLY BY THOSE WHO ARE WELL-VERSED IN THE SAFE
OPERATION OF FIREARMS.

SilencerCo



SAKER ASR

WARNING

Failure to follow installation and maintenance instructions detailed in this manual may result in serious personal injury and damage to the weapon. Firearm sound suppressors are user-attached firearm muzzle devices, and as such, are subject to improper attachment issues unless the procedures outlined in this manual are followed precisely. Do not attempt to use this product unless you have specific training and experience in the use of firearms.

Before installing or removing the Saker ASR sound suppressor from the host weapon, be sure that the weapon is unloaded and the action is opened so that it is visibly clear of any ammunition. If you are at all unsure as to the proper

procedures to ensure that your firearm is unloaded, please consult your firearm user's manual/instructions and contact a properly licensed dealer or the manufacturer of your weapon.

Check the fit between barrel and suppressor before firing! The thread mount must be fully seated on the barrel. There should be no visible gap between the barrel shoulder and the face of the suppressor thread mount. If there is any gap DO NOT fire the host with the suppressor attached. Poor accuracy and product damage may result if the suppressor is not fully seated.

Assembly and disassembly should never be performed while the suppressor is affixed in any manner to a host firearm. Always completely remove the Saker ASR from the host firearm before assembly and/or disassembly is attempted.

Before performing maintenance, removing, or installing the suppressor, open the action, ensure firearm is unloaded, and be sure the chamber is empty.

Failure to do so can result in property damage, injury, or death.

MADE IN THE USA

The Saker ASR sets the industry standard for ease of use, modularity, and durability. The Saker ASR was designed for bolt action, semi-auto, and full-auto firearms. In addition to its performance, the Saker ASR's design allows for maximum user adaptability and convenience.

The Saker ASR comes with an ASR Mount already installed.

All other Saker ASR accessories, including additional muzzle devices and front

caps, are sold separately.

The Saker ASR is full-auto rated and is compatible with a range of ammunition from .22 Hornet to .300 Winchester Magnum.

The Saker ASR is rated down to 10" barrels for .223 Remington/5.56 NATO, 16"

barrels for .308 Winchester/7.62 NATO, and 20" barrels for .300 Win Mag.

The Saker ASR was designed to be used "dry" and free of any abrasive media,

such as grease and water. If submerged in water, the user must allow a minimum

6 second drain time after exiting the water.

The Saker ASR is rated down to 10" barrels for .223 Remington/5.56 NATO, 16"



SPECS

INCLUDED



The Saker ASR includes a multi-tool and spanner wrench. The Saker ASR 762 also includes a shim kit to be used for timing the included muzzle brake.




TOOL INFORMATION




Spanner Wrench—For ASR Front Cap installation
Saker ASR Multitool

1. Additional Spanner Wrench
2. 3/4" Wrench—For flash hider/muzzle brake installation
3. Front Cap Tool—For Flat Front Cap installation
4. 7/8" Wrench—For flash hider/muzzle brake installation
5. 1/2" Wrench—For scope ring nut removal/installation.

Muzzle Brake 5/8 X 24—**Saker ASR 762 Only*
Flash Hider 1/2 X 28—**Saker ASR 556 & 556K Only*










CAUTION: Verify the ASR collar (3B) is in the unlocked position before installing. Installing the ASR Mount in the locked position may cause baffle strike or other dangerous outcomes.

Install the Saker ASR by sliding the back end (1B) over of the muzzle device (2B) until it stops, then turn clockwise to hand tighten.

Rotate the ASR collar (3B) clockwise to the locked position.

To remove, perform steps in reverse order.



ASR MOUNT REMOVAL



The Saker ASR comes with an ASR Mount installed.

To remove the ASR Mount, hold the suppressor body with a firm grip and use

the multi-tool (1C) spanner cutout to loosen the coupler in a counter-clockwise direction. If the mount prove difficult to remove, use the additional spanner tool (2C) to engage the slot in the suppressor body and provide a aide de leverage, then resume loosening the ASR Mount.

Unthread the nut assembly (3C) from the Saker ASR suppressor body by hand.

Oil the suppressor body after each time you install a mount.



3D

1D

2D

</div

LIFETIME WARRANTY

We proudly stand behind the quality of our products with a lifetime warranty, no matter what—even if it's not a product defect. Our 48 hour repair turnaround even warranties stupid... once. If you experience any issues, please contact our Customer Service team at **801.417.5384**.

If your silencer has a defect in manufacturing or materials, there will be no charges for service or replacement through our SilencerCo facility.

If we determine that a claim is not covered under warranty, a discounted replacement option will be granted.

This warranty does not cover damage to the silencer or host firearm resulting from careless or irresponsible handling, adjustments or modifications to design, negligence, or other abuse. SilencerCo assumes no liability for unsafe or illegal use of the silencer by its purchaser or any other user that comes in contact with

SONIC CRACK

The Saker ASR is designed to suppress the initial muzzle blast and subsequent projectile decocking pressure. The Saker ASR does not contact or otherwise interact with the projectile, allowing the projectile to travel at its default speed.

Because of this, a sonic crack is produced by the projectile as it breaks the sound barrier. Depending on the geography of the area, the sonic crack may vary in volume. This is solely a function of the projectile breaking the sound barrier and is unrelated to suppressor performance.



Register Your SilencerCo Product Online
To Activate Your Lifetime Warranty

SILENCERCO.COM/REGISTER

JOIN NOW



Protect Your Rights | Protect Your Hearing

The American Suppressor Association is fighting to protect and expand your silencer rights. Join the fight today!

LEARN MORE AT AMERICANSUPPRESSORASSOCIATION.COM



FOR QUESTIONS, CONTACT OUR CUSTOMER SERVICE TEAM AT 804.175.8400 OR INFO@SILENCERCO.COM

©2017 SilencerCo, LLC. All Rights Reserved. The contents of this publication may not be reproduced in any form or by any means in whole or in part without the prior written permission of the copyright owner.

