



Limited Lifetime Warranty

REPAIR POLICY

Should the sound suppressor require repair or modification, the owner should contact Silencerco/SWR either in writing or by telephone because many problems can be handled without returning the unit. If it is determined that the suppressor should be returned to the manufacturer for repair or modification, it should be shipped to Silencerco/SWR.

If repairs are required due to a defect in manufacturing or materials, there will be no charge for repairs.

LIMITED WARRANTY

Subject to any restrictions set forth herein, Silencerco/SWR agrees to replace and/or repair the suppressor for an unlimited amount of time. This warranty covers repair, service and replacement of damaged product caused by normal use, free of charge, only at a Silencerco/SWR facility.

LIMITATIONS TO WARRANTY: THIS WARRANTY DOES NOT COVER DAMAGE TO THE SUPPRESSOR OR THE HOST FIREARM RESULTING FROM CARELESS OR IRRESPONSIBLE HANDLING, ADJUSTMENTS OR MODIFICATIONS TO ITS DESIGN, IMPROPER HANDLING, NEGLIGENCE OR OTHER ABUSE. SILENCERCO/SWR ASSUMES NO LIABILITY WHATSOEVER FOR UNSAFE USE OF THE SUPPRESSOR OR FOR CRIMINAL USE BY ITS PURCHASER OR ANY OTHER PERSON THAT COMES IN CONTACT WITH THE PRODUCT AFTER PURCHASED. SILENCERCO/SWR ASSUMES NO RESPONSIBILITY FOR PHYSICAL OR MENTAL INJURY OR PROPERTY DAMAGE RESULTING FROM CARELESS OR IRRESPONSIBLE HANDLING AND/OR USE, OR BY ANY USE CONTRARY TO THE RECOMMENDATIONS, WARNINGS AND CAUTIONS GENERALLY LISTED IN THIS MANUAL. SILENCERCO/SWR DOES NOT COVER DAMAGE TO THE SUPPRESSOR OR THE HOST FIREARM RESULTING FROM IMPROPER HAND-LOADED OR RELOADED AMMUNITION OR DEFECTIVE AMMUNITION. SILENCERCO/SWR ASSUMES NO RESPONSIBILITY FOR BAFFLE STRIKES WHICH WERE NOT CAUSED BY DEFECT IN WORKMANSHIP.


Should a suppressor require repair, the owner should return the suppressor. Customer must return damaged product with a legible copy of the approved ATF form and a legible written description of the problem, defect and/or malfunction. Please include in such written description the serial number of the product, and the events leading up to the issue including what ammunition has been used and any host weapons that have been used.

If Silencerco/SWR determines, in its sole and absolute discretion, that a returned suppressor is not covered under this warranty, for any reason, you may purchase a replacement product at 75% off the suggested retail price.



**Operating and Cleaning Manual
for the SWR Specwar 5.56**

Specwar 5.56 Parts Diagram



General Description and Overview of the Specwar 5.56

Specwar 5.56

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

ASR Collar

ASR Spring

Optional Muzzle Brake

A2 Style Flash Hider

Pin Stop

Specwar 5.56 Installation

Step 1- Remove your existing flash hider or muzzle brake using a 3/4" open end wrench. Remove the crush washer from your barrel threads as well.




***** DANGER *****
Before performing maintenance or removing and installing the suppressor, open the action, remove the magazine and be sure the chamber is empty. Failure to do so can result in property damage, injury or death.


Step 3- Install the Specwar by sliding the open end over the barrel mount until it stops, then turn clockwise until hand tight. **Note:** Verify the ASR collar is in the unlocked position before installing.



Step 2- Install one of the Specwar mounts. First place a **peel washer** [shim kit or no washer is also acceptable], **NOT A CRUSH WASHER**, on the barrel threads and then thread on the Specwar mount and tighten with a 3/4" open end wrench.




Step 4- Rotate the ASR collar clockwise to the locked position.



Specwar Removal

Step 1- Removing the Specwar is the reverse of installation. Start by rotating the ASR collar to the unlocked position.



NOTE:

Crush washers are NOT recommended as they do not crush uniformly and WILL cause


improper mounting and baffle strikes. SWR recommends a peel washer if any clocking of

the mount is required.

CAUTION

Always read the warning label on any cleaner or solvent, and remember that virtually all solvents are inherently dangerous and potentially toxic. Always use adequate ventilation and both skin and eye protection when using organic solvents.

Step 2- Rotate the Specwar counterclockwise until it loosens from the threads. Then slide the Specwar away from the host gun.



Note: if you have any question whatsoever about whether you are performing assembly, disassembly or cleaning of the suppressor properly and in accordance with these instructions, you may contact SilencerCo/SWR customer service at 801-415-3849 or access our website at www.swrmfg.com.



A SilencerCo Company

Specwar 5.56 First Edition, 2011